

## ELECTRIC SERIES SCISSOR LIFTS

# 1412E PLUS(4647E PLUS)/1414E PLUS(4655E PLUS)

Complies with ISO/CE/ANSI/AS/CSA/EAC/CU-TR standards

## PRODUCT HIGHLIGHTS

### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

### Reduced maintenance costs

- The short design of sliding rail makes debris easy to clean
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

### Reliable performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding rail designed for anti-scratch



### Standard features

Maintenance-free battery	Automatic braking system	Drive at full height
Full proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresic paint technology
2WSx2WD	Fault diagnosis system	Foldable guardrail
Non-marking tyres	Tilt protection	Overload sensing system
PCU bracket	Automatic pothole guard	AC power to platform with RCBO

### Optional features

Overhead anti-collision device	Headlight	
	Foot switch	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.EU | INFO@SINOBOOM.EU | +31 180 225 666  
Nikkelstraat 26, 2984 AM Ridderkerk, The Netherlands

ELECTRIC SERIES SCISSOR LIFTS

# 1412E PLUS(4647E PLUS)/1414E PLUS (4655E PLUS)

Complies with ISO/CE/ANSI/AS/CSA/EAC/CU-TR standards

Model	1412E Plus(4647E Plus)	1414E Plus(4655E Plus)
<b>Dimensions</b>		
Max Working Height	15.8m(51'10")	15.8m(51'10")indoor 10.5m(34'5")outdoor
A Max Platform Height	13.8m(45'3")	13.8m(45'3")indoor 8.5m(27'11")outdoor
B Max Horizontal Extension	0.9m(3')	0.9m(3')
C Length-Stowed	2.78m(9')	2.78m(9')
D Width-Stowed	1.27m(4'2")	1.41m(4'7")
E Height-stowed (Rail Folded)	1.96m(6'5")	1.98m(6'6")
E Height-stowed (Rail Unfolded)	2.6m(8'6")	2.6m(8'6")
F Wheelbase	2.22m(7'3")	2.22m(7'3")
Ground Clearance(Pothole Guard Stowed)	0.1m(4")	0.1m(4")
Ground Clearance(Pothole Guard Deployed)	25mm(0.98")	25mm(0.98")
Platform Dimensions(LxWxH)	2.64mx1.15mx1.1m (8'8"x3'9"x3'7")	2.64mx1.3mx1.1m (8'8"x4'3"x3'7")
<b>Performance</b>		
Platform Allowable Occupants (Indoors/Outdoors)	2 persons/-	2persons/1 person
Platform Capacity	350kg(772lbs)	350kg(772lbs)
Drive Speed-Stowed	4km/h(2.5mph)	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)	0.8km/h(0.5mph)
Elevation Time(Unloaded)	75s-85s	75s-85s
Descent Time(Unloaded)	55s-63s	55s-63s
Gradeability	25%	20%
Turning Radius(Inside/Outside)	0/2.64m(0/8'8")	0/2.64m(8'8")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	3°/1.5°
Tire Spec/Type	380x125mm(15x5")/solid	380x125mm(15x5")/solid
<b>Power</b>		
Batteries	4x12V,140 Ah	4x12V,140 Ah
Power Source	24V DC, 280 Ah	24V DC, 280 Ah
Drive Mode	Motor, front-wheel	Motor, front-wheel
Charger Input	100~240V AC	100-240 V DC
Charger Output	30A	30A
Hydraulic Tank Capacity	15L(3.3gal(UK)/ 3.9gal(US))	15L(3.3gal(UK)/ 3.9gal(US))
<b>Weight</b>		
Weight	3,375kg(7,442lbs)	3,660kg(8,069lbs)
Standards Compliance		ISO/CE/ANSI/AS/CSA/EAC/CU-TR

